

LPQ58 2" Direct Thermal Label Printer

- Fashionable design
- Unique media supply spindle design, supports three types of label roll inner core diameter
- Printer head quick replacement design, convenient for service
- Fully-closed gear box design, no dust going in, high reliability
- Easy loading design, quick paper roll placement
- With optional external paper roll holder, support supper big paper roll
- Adjustable black mark position, catering to different label paper
- Front paper-out design, water-splash resistant
- Bundled with Bartender label design software & Seagull Windows Driver



Printer Head Quick Replacement



Adjustable Paper Shaft Design



Fashionable Design



Specification

Item	Parameter	
Printing	Printing Method	Direct thermal line printing
	Resolution	203dpi(8dots/mm)
	Printing Speed	3IPS Max
	Printing Width	56mm Max
	Printing Length	400mm
Processor	32 bit RISC CPU	
Memory	RAM	2MB
	Flash	2MB
Detection	Sensors	Out of paper detection, Gap detection, Notch detection, Black mark detection, TPH temperature detection
Media	Types	Fan-fed or Roll-fed, Die-cut or Continuous label
	Width	1''(25mm) – 2.44''(62mm)
	Thickness	0.003''(60um) – 0.007''(180um)
	Label Roll Diameter	90mm
	Core Diameter	0.5''(12.7mm), 1''(25.4mm), 1.5''(38.1mm)
Programming Language	TSPL Simulation	
Software	Label Design	Bartender Ultralife
	Driver	Windows 2000,XP,Vista,8,10 By Seagull
Resident Fonts	Bitmap Fonts	6, 8, 12, 16, 32, OCR A & B. 90°, 180°, 270° rotatable and 10 times expandable in horizontal and vertical directions

Code Pages		39
Barcode	1D	31
	2D	PDF417Data matrix code, Maxi Code, QR code, Micro PDF417, Micro QR code, Aztec code
Interfaces	USB, RS232C	
Control Panel	Tri-color status LED, Power and Feed button	
Power Adapter	Power Input	AC100V ~240V 50/60Hz 1.5A
	Power Supply	DC12V/2A
Environment	Operation	41°F - 104°F(5°C-40°C), 30% - 85% no condensing
	Storage	-4°F - 122°F(-20°C-50°C), 10% - 50% no condensing
Physical	Dimension	186(L)*133(W)*128(H)mm
Characteristics	Weight	805g, excluding consumables
Optional Accessories	External label roll holder	
Agency Approvals	CCC, FCC, CE	



Logistic



Medical



Retail



Restaurant



Barcode



Easy Loading



Compact design



Windows